
LOXONE

Datasheet

Room Comfort Sensor Air Anthracite (Temperature, Humidity)

Part No: 100265



About the product

The Loxone Room Comfort Sensor Air is used to measure **temperature and humidity** in rooms.

Electrical Specifications

Power Supply	9 ... 28VDC or 2x 1.5V AAA batteries
Power consumption	battery: typ. 0.02mW, max. 0.050W external power supply: typ. 0.065W, max. 0.085W
Power loss	max. 0.085W
Battery lifetime	up to 2 years
Temperature detection range	-40 … 125°C / -40 … 257°F; +/- 0.5°C / 0.9°F
Humidity detection range	0 … 100% r.H. +/- 2%, (non condensing)


Interfaces

Loxone Air	868MHz (SRD Band Europe), 4 channels available max. Power 15.1mW e.r.p. 915MHz (ISM Band Region 2), 10 channels available max. Power 13.2mW internal antenna

Connection Terminals

Wire cross-section	0.25 … 0.8 mm² / AWG 23 … 18
Stripping length	5 mm / 0.2"
Temperature resistance	-40 … 105 °C / -40 … 221 °F


Connection Diagram

Connection Diagram	

Product Characteristics

Colours	Anthracite: RAL7021
Finish	Matte

Weight & Dimensions

Net weight	46g
Total weight	142 g
Product dimensions	80x80x17.4mm / 3.15x3.15x0.69" (LxWxH) with frame 55.8x55.8x32.9mm / 2.19x2.19x1.30" (LxWxH) freestanding
Product dimensions drawing	
Pack size	194x122x22mm / 7.64x4.80x0.87" (LxWxH)

Certifications & Standards

Safety class	IP20
Certifications	CE UKCA

Installation must be carried out by a qualified electrician in accordance with the relevant regulations.

Published by

LOXONE

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com


Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

LOXONE

Datenblatt

Raumklima Sensor Air Anthrazit (Temperatur, Feuchte)

Part No: 100265



Über das Produkt

Der Loxone Raumklima Sensor Air dient zur Messung von **Temperatur und Luftfeuchtigkeit** in Räumen.

Elektrische Spezifikationen

Spannungsversorgung	9 ... 28VDC oder 2x 1,5V AAA Batterien
Leistungsaufnahme	Batterie: typ. 0,02mW, max. 0.050W externe Spannungsversorgung: typ. 0.065W, max. 0.085W
Verlustleistung	max. 0.085W
Batterie Lebensdauer	bis zu 2 Jahre
Messbereich Temperatursensor	-40 … 125°C / -40 … 257°F; +/- 0.5°C / 0.9°F
Messbereich Luftfeuchtigkeitssensor	0 … 100% r.H. +/- 2%, (nicht kondensierend)


Schnittstellen

Loxone Air	Loxone Air: 868MHz (SRD Band Europa), 4 Kanäle wählbar max. Sendeleistung 15,1mW e.r.p. 915MHz (ISM Band Region 2), 10 Kanäle wählbar max. Sendeleistung 13,2mW interne Antenne

Anschlussklemmen

Leiterquerschnitt	0,25 … 0,8 mm² / AWG 23 … 18
Abisolierlänge	5 mm / 0,2"
Temperaturbeständigkeit	-40 … 105 °C / -40 … 221 °F


Anschlussplan

Anschlussplan	

Produkteigenschaften

Farbe	Anthrazit: RAL7021
Glanzgrad	Matt

Gewicht & Abmessungen

Nettogewicht	46g
Bruttogewicht	142 g
Produktmaße	80x80x17,4mm / 3,15x3,15x0,69" (LxBxH) mit Rahmen 55,8x55,8x32,9mm / 2,19x2,19x1,30" (LxBxH) freistehend
Produktmaßzeichnung	
Packmaß	194x122x22mm / 7,64x4,80x0,87" (LxBxH)

Zertifizierungen & Standards

Schutzklasse	IP20
Zertifizierungen	CE UKCA

Die Installation muss von einer qualifizierten Elektrofachkraft gemäß den einschlägigen Vorschriften durchgeführt werden.

Veröffentlicht von

LOXONE

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom